DOW Dow AgroSciences

Material Safety Data Sheet

Dow AgroSciences India Pvt. Ltd.

Product Name: PREDATOR (TM) Insecticide Issue Date: 2014/03/18
Print Date: 02 May 2019

Dow AgroSciences India Pvt. Ltd. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Identification of the substance/preparation and of the company/undertaking

Product Name

PREDATOR ™ Insecticide

COMPANY IDENTIFICATION

Dow AgroSciences India Pvt. Ltd. A Subsidiary of The Dow Chemical Company 1st Floor, Block B, 02, Godrej IT Park Pirojshanangar, L.B.S. Marg Vikhroli Mumbai, MA 400 079 India

Customer Information Number: 91 22 6674 1700

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 91-2356-272046 **Local Emergency Contact**: 91 22 66741800

2. Composition/information on ingredients

| Component | Amount | Classification: | CAS# | EC# |
|---|-----------------------------|---|-------------------------|------------------------|
| chlorpyrifos (ISO) Solvent naphtha (petroleum), heavy aromatic | 50.3 % > 30.0 - < 40.0 % | T: R25; N: R50/53 Xn: R65; Carc. 3: R40; R66; N: R51/53 | 2921-88-2 64742-94-5 | 220-864-4 265-198-5 |
| Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha | > 10.0 - < 20.0 % | Xn: R65; R66; R10; R67; N: R51/53 | 64742-82-1 | 265-185-4 |
| sulfotep (ISO) | < 1.0 % | T+: R27/28; N: R50, R53 | 3689-24-5 | 222-995-2 |

See Section 16 for full text of R-phrases.

3. Hazards Identification

May cause cancer.

Toxic if swallowed.

Harmful in contact with skin and if swallowed.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. First-aid measures

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice. If breathing is difficult, oxygen should be administered by qualified personnel.

Skin Contact: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Suitable emergency safety shower facility should be available in work area.

Eye Contact: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. Suitable emergency eye wash facility should be available in work area.

Ingestion: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of immediate medical attention and special treatment needed

Chlorpyrifos is a cholinesterase inhibitor. Treat symptomatically. In case of severe acute poisoning, use antidote immediately after establishing an open airway and respiration. Atropine, only by injection, is the preferable antidote. Oximes, such as 2-PAM/protopam, may be therapeutic if used early; however, use only in conjunction with atropine. Attempt seizure control with diazepam 5-10 mg (adults) intravenous over 2-3 minutes. Repeat every 5-10 minutes as needed. Monitor for hypotension, respiratory depression, and need for intubation. Consider second agent if seizures persist after 30 mg. If seizures persist or recur administer phenobarbital 600-1200 mg (adults) intravenous diluted in 60 ml 0.9% saline given at 25-50 mg/minute. Evaluate for hypoxia, dysrhythmia, electrolyte disturbance, hypoglycemia (treat adults with dextrose 100 mg intravenous). Maintain adequate ventilation and oxygenation of the patient. If exposed, plasma and red blood cell cholinesterase tests may indicate significance of exposure (baseline data are useful). If burn is present, treat as any thermal burn, after decontamination. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or doctor, or going for treatment.

5. Fire Fighting Measures

Suitable extinguishing media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Sulfur oxides. Phosphorous compounds. Nitrogen oxides. Hydrogen chloride. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. When product is stored in closed containers, a flammable atmosphere can develop. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Consider feasibility of a controlled burn to minimize environment damage. Foam fire extinguishing system is preferred because uncontrolled water can spread possible contamination. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. Spills or discharge to natural waterways is likely to kill aquatic organisms.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact Dow AgroSciences for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

7. Handling and Storage

Handling

Product Name: PREDATOR (TM) Insecticide

General Handling: Keep out of reach of children. Keep away from heat, sparks and flame. Do not swallow. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Electrically ground and bond all equipment. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Issue Date: 2014/03/18

Other Precautions: Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Storage

Store in a dry place. Store in original container. Keep container tightly closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies. Minimize sources of ignition, such as static build-up, heat, spark or flame. Avoid temperatures above 50°C (122°F)

8. Exposure Controls / Personal Protection

| Exposure Limits | | | |
|---|-------|--|---------------------|
| Component | List | Туре | Value |
| chlorpyrifos (ISO) | ACGIH | TWA Inhalable fraction and vapor. | 0.1 mg/m3 SKIN, BEI |
| Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha | ACGIH | TWA | 100 ppm |

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING. A BEI notation following the exposure guideline refers to a guidance value for assessing biological monitoring results as an indicator of the uptake of a substance from all routes of exposures. A "skin" notation following the inhalation exposure guideline refers to the potential for dermal absorption of the material including mucous membranes and the eyes either by contact with vapors or by direct skin contact.

It is intended to alert the reader that inhalation may not be the only route of exposure and that measures to minimize dermal exposures should be considered.

Personal Protection

Eye/Face Protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent. If exposure causes eye discomfort, use a full-face respirator.

Skin Protection: When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for

a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Issue Date: 2014/03/18

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Ingestion: Avoid ingestion of even very small amounts; do not consume or store food or tobacco in the work area; wash hands and face before smoking or eating.

Engineering Controls

Ventilation: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

9. Physical and Chemical Properties

Appearance

Physical StateLiquid.ColorBrownOdorAromatic

Odor Threshold

pH

No test data available

No test data available

Melting Point Not applicable

Freezing Point No test data available No test data available.

Flash Point - Closed Cup > 50 °C

Evaporation Rate (Butyl No test data available

Acetate = 1)

Flammable Limits In Air

Lower: No test data available
Upper: No test data available

Vapor Pressure No test data available Vapor Density (air = 1) No test data available

Specific Gravity (H2O = 1)

Solubility in water (by

1.117

emulsifiable

weight)

Partition coefficient, n- No data available for this product. See Section 12 for individual

octanol/water (log Pow)component data.Autoignition TemperatureNo test data availableDecompositionNo test data available

Temperature

Explosive propertiesNo test data available **Oxidizing properties**No test data available

Liquid Density 1.115 g/ml

10. Stability and Reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Unstable at elevated temperatures.

Possibility of hazardous reactions

Polymerization will not occur.

Conditions to Avoid: Avoid temperatures above 50°C (122°F) Active ingredient decomposes at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible Materials: Avoid contact with oxidizing materials. Avoid contact with: Bases. Strong acids.

Hazardous decomposition products

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Hydrogen chloride. Organic sulfides. Sulfur dioxide. Toxic gases are released during decomposition.

11. Toxicological Information

Acute Toxicity

Ingestion

Moderate toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause serious injury, even death.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): Estimated. LD50, rat 400 mg/kg

Aspiration hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

Dermal

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): Estimated. LD50, rabbit > 5,000 mg/kg

Inhalation

Prolonged excessive exposure may cause adverse effects. May cause central nervous system effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

As product: The LC50 has not been determined.

Eye damage/eye irritation

May cause slight eye irritation. Corneal injury is unlikely. Vapor may cause eye irritation experienced as mild discomfort and redness.

Skin corrosion/irritation

Prolonged contact may cause slight skin irritation with local redness. Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage. May cause drying and flaking of the skin.

Sensitization

Skin

For the active ingredient(s): Did not cause allergic skin reactions when tested in guinea pigs.

Respiratory

No relevant data found.

Repeated Dose Toxicity

For the active ingredient(s): Excessive exposure may produce organophosphate type cholinesterase inhibition. Signs and symptoms of excessive exposure to active ingredient may be headache, dizziness, incoordination, muscle twitching, tremors, nausea, abdominal cramps, diarrhea, sweating, pinpoint pupils, blurred vision, salivation, tearing, tightness in chest, excessive urination, convulsions. In animals, effects have been reported on the following organs: Adrenal gland. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use. Excessive exposure to solvent(s) may cause respiratory irritation and central nervous system depression.

Chronic Toxicity and Carcinogenicity

For the active ingredient(s): Did not cause cancer in laboratory animals.

Developmental Toxicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Reproductive Toxicity

For the active ingredient(s): Chlorpyrifos did not interfere with fertility in reproduction studies in laboratory animals. Some evidence of toxicity to the offspring occurred, but only at a dose high enough to produce significant toxicity to the parent animals.

Genetic Toxicology

For the active ingredient(s): Based on a majority of negative data and some equivocal or marginally positive results, active ingredient is considered to have minimal genetic toxicity potential. For the solvent(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. **Ecological Information**

Toxicity

Data for Component: chlorpyrifos (ISO)

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species). Material is highly toxic to birds on a dietary basis (LC50 between 50 and 500 ppm).

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), 96 h: 0.003 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Water flea), 48 h: 0.0001 mg/l

Aquatic Plant Toxicity

EbC50, alga Scenedesmus sp., 72 h: 0.580 mg/l

Toxicity to Micro-organisms

EC50; activated sludge: > 100 mg/l

Fish Chronic Toxicity Value (ChV)

Pimephales promelas (fathead minnow), 216 d. NOEC:0.000568 mg/l

Aquatic Invertebrates Chronic Toxicity Value

Daphnia magna (Water flea), number of offspring, NOEC: 0.000056 mg/l

Toxicity to Above Ground Organisms

dietary LC50, Anas platyrhynchos (Mallard duck): 203 mg/kg diet.

oral LD50, Apis mellifera (bees): 0.36 micrograms/bee contact LD50, Apis mellifera (bees): 0.070 micrograms/bee

Toxicity to Soil Dwelling Organisms

LC50, Eisenia fetida (earthworms), 14 d: 129 mg/kg

Data for Component: Solvent naphtha (petroleum), heavy aromatic

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species). Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg). Material is practically non-toxic to birds on a dietary basis (LC50 > 5000 ppm).

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), 96 h: 3.0 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Water flea), 48 h, immobilization: 1.1 mg/l

Aquatic Plant Toxicity

EC50, Pseudokirchneriella subcapitata (green algae), 72 h: 7.9 mg/l

Aquatic Invertebrates Chronic Toxicity Value

Daphnia pulex (Water flea), 21 d, mortality, NOEC: 5.2 mg/l

Toxicity to Above Ground Organisms

dietary LC50, Colinus virginianus (Bobwhite quail): > 6500 mg/kg diet.

oral LD50, Colinus virginianus (Bobwhite quail): > 2250 mg/kg bodyweight.

Data for Component: Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

Fish Acute & Prolonged Toxicity

LL50, fathead minnow (Pimephales promelas), semi-static test, 96 h: 8.2 mg/l

Aquatic Invertebrate Acute Toxicity

EL50, Daphnia magna (Water flea), static test, 48 h: 4.5 mg/l

Aquatic Plant Toxicity

EL50, alga Scenedesmus sp., static, Growth rate inhibition, 72 h: 3.1 mg/l

Fish Chronic Toxicity Value (ChV)

fathead minnow (Pimephales promelas), semi-static test, 14 d, mortality, NOEC, NOEC:2.6 mg/l

Issue Date: 2014/03/18

Aquatic Invertebrates Chronic Toxicity Value

water flea Daphnia magna, semi-static test, 21 d, number of offspring, NOEC, NOEC: 2.6 mg/l Data for Component: **sulfotep (ISO)**

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species).

Fish Acute & Prolonged Toxicity

LC50, Lepomis macrochirus (Bluegill sunfish), 96 h: 0.0016 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, Daphnia magna (Water flea), 48 h, immobilization: 0.00023 mg/l

Toxicity to Above Ground Organisms

oral LD50, Colinus virginianus (Bobwhite quail): > 5,000 ppm

Persistence and Degradability

Data for Component: chlorpyrifos (ISO)

Material is not readily biodegradable according to OECD/EEC guidelines.

Stability in Water (1/2-life):

72 0

OECD Biodegradation Tests:

| Biodegradation | Exposure Time | Method | 10 Day Window |
|--|---------------|----------------|---------------|
| 22 % | 28 d | OECD 301D Test | fail |
| Indirect Photodegradation with OH Radicals | | | |
| Rate Constant | Atmosphe | ric Half-life | Method |
| 9.0E-11 cm3/s | 1.4 | 1 h | Estimated. |
| | | • | • |

Theoretical Oxygen Demand: 2.46 mg/mg

Data for Component: Solvent naphtha (petroleum), heavy aromatic

Biodegradation may occur under aerobic conditions (in the presence of oxygen). Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

OECD Biodegradation Tests:

| Biodegradation | Exposure Time | Method | 10 Day Window |
|----------------|---------------|----------------|---------------|
| 30 - 41 % | 28 d | OECD 301D Test | fail |

<u>Data for Component:</u> Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha

Material is expected to be readily biodegradable.

Data for Component: sulfotep (ISO)

No relevant information found.

Bioaccumulative potential

Data for Component: chlorpyrifos (ISO)

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient, n-octanol/water (log Pow): 4.7 Estimated.

Data for Component: Solvent naphtha (petroleum), heavy aromatic

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient, n-octanol/water (log Pow): 2.9 - 6.1 Measured

Bioconcentration Factor (BCF): 61 - 159; Fish

<u>Data for Component: Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha</u>

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7)

Partition coefficient, n-octanol/water (log Pow): 2.1 - 6 Estimated.

Data for Component: sulfotep (ISO)

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log

Pow between 3 and 5).

Partition coefficient, n-octanol/water (log Pow): 3.99

Mobility in soil

Data for Component: chlorpyrifos (ISO)

Mobility in soil: Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient, soil organic carbon/water (Koc): 8,151Henry's Law Constant (H):

4.78E-01 Pa*m3/mole.

Data for Component: Solvent naphtha (petroleum), heavy aromatic

Mobility in soil: No relevant data found.

Data for Component: Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point

hydrogen treated naphtha

Mobility in soil: Expected to be relatively immobile in soil (Koc > 5000).

Data for Component: sulfotep (ISO)

Mobility in soil: Potential for mobility in soil is slight (Koc between 2000 and 5000).

Henry's Law Constant (H): 1.23E-06 atm*m3/mole

13. Disposal Considerations

If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

14. Transport Information

ROAD & RAIL

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. **Technical Name:** Solvent Naphtha and Chlorpyrifos

Hazard Class: 3 ID Number: UN1993 Packing Group: PG III

Classification: F1

Hazard identification No: 30 Environmental Hazard: Yes

OCEAN

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. **Technical Name:** Solvent Naphtha and Chlorpyrifos

Hazard Class: 3 ID Number: UN1993 Packing Group: PG III

EMS Number: F-E,S-E Marine pollutant: Yes

ΔIR

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Technical Name: Solvent Naphtha and Chlorpyrifos

Hazard Class: 3 ID Number: UN1993 Packing Group: PG III

Cargo Packing Instruction: 366 Environmental Hazard: Yes

INLAND WATERWAYS

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. Technical Name: Solvent Naphtha and Chlorpyrifos ID Number: UN1993 Packing Group: PG III

Classification: F1

Hazard identification No: 30 Environmental Hazard: Yes

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

European Inventory of Existing Commercial Chemical Substances (EINECS)

The components of this product are on the EINECS inventory or are exempt from inventory requirements.

Classification and User Label Information

Hazard Symbol:

T - Toxic.

N - Dangerous for the environment.

Risk Phrases:

R45 - May cause cancer.

R25 - Toxic if swallowed.

R21/22 - Harmful in contact with skin and if swallowed.

R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases:

S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S53 - Avoid exposure - obtain special instructions before use.

S36/37 - Wear suitable protective clothing and gloves.

S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.

Contains: chlorpyrifos (ISO)

Solvent naphtha (petroleum), heavy aromatic

Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated

naphtha sulfotep (ISO)

16. Other Information

Risk-phrases in the Composition section

R10 Flammable.

| R25 | Toxic if swallowed. |
|--------|--|
| R27/28 | Very toxic in contact with skin and if swallowed. |
| R37 | Irritating to respiratory system. |
| R40 | Limited evidence of a carcinogenic effect. |
| R50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |

Revision

Identification Number: 77505 / 4068 / Issue Date 2014/03/18 / Version: 3.1

DAS Code: GF-1351

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

| N/A | Not available |
|---------|---|
| W/W | Weight/Weight |
| OEL | Occupational Exposure Limit |
| STEL | Short Term Exposure Limit |
| TWA | Time Weighted Average |
| ACGIH | American Conference of Governmental Industrial Hygienists, Inc. |
| DOW IHG | Dow Industrial Hygiene Guideline |
| WEEL | Workplace Environmental Exposure Level |
| HAZ_DES | Hazard Designation |

Dow AgroSciences India Pvt. Ltd. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.